

MORBARK® 6600 TRACK WOOD HOG

FEATURES

- » Variable speed infeed system consists of one 36" (91.44 cm) diameter top compression feed roll with internal drive and a 12'6" long x 64" (3.81 m x 162 cm) wide live floor equipped with five strands of WDH-120 chain in a staggered configuration with 4'7" (1.3 m) long hydraulically operated folding infeed extension
 - » 42" x 66 5/8" (106.7 cm x 169 cm) Hammermill system constructed of heavy-duty 28" (71.12 cm) diameter rotor, (18) 1 3/8" (46.67 cm) thick two-piece laser-cut rotor plates keyed on a 9" (22.86 cm) diameter shaft with 5 3/16" (13.17 cm) bearings and eight 2 1/2" (6.35 cm) hammer retaining rods. Hammermill pattern has (18) 2 1/4" (5.71 cm) balanced forged steel hammers, (18) 3 5/8" (9.2 cm) wide double-edged replaceable inserts and 18 forged rakers
 - » Hydraulic hinged door allows quick and easy access for changing grates
 - » Automatic reversing fan system
 - » Dust suppression system
 - » Hydraulically operated debris containment door
 - » Discharge system consists of a hydraulically driven, horizontal 48" wide x 19' (121.92 cm x 5.79 m) long aggregate belly belt conveyor discharging onto a 40" (101.6 cm) wide stacking conveyor with hydraulic fold for transport
 - » Remote control with tethered back-up system
 - » Magnetized end pulley with collecting slide tray for ferrous metal removal
 - » 11-HP (8.2 kW) air compressor with lockable enclosure
- ## OPTIONS
- » 330L Caterpillar Undercarriage
 - » 14-knife chipper drum assembly
 - » Hydraulic rod puller



Morbark Integrated Control System (MICS)

Internal Planetary Drive Feed System

Externally Adjustable Break-away Torque Limiter



SPECIFICATIONS

| | US | METRIC |
|-------------------------|-------------------------------|-----------------|
| Length (transportation) | 44'9" | 13.64 m |
| Length (operating) | 67'1" | 20.45 m |
| Height (transport) | 11'11" | 3.63 m |
| Height (operating) | 18'6" | 5.69 m |
| Width | 11'11" | 3.63 m |
| Gross Weight (approx.) | 109,120 lbs | 49,500 kg |
| Engine | CAT | |
| Horsepower | 1,125 to 1,200 HP | 838 to 894 HP |
| Fuel Capacity (tank) | 390 gallons | 1,478 litre |
| Hydraulic Oil | 335 gallons | 1,268 litre |
| Infeed Opening | 66" x 50" | 167 cm x 127 cm |
| Tracks | SS40 Strickland Undercarriage | |



MORBARK®

www.morbark.com

800.831.0042

SPECIFICATIONS MAY VARY WITH EQUIPMENT OPTIONS

2/15/17